



airo-chemie
A. Schmiemann GmbH & Co. KG
chemisch-technische Produkte
D-40736 Langenfeld · Postfach 1143
D-40764 Langenfeld · Carl-Leverkus-Str. 27
Tel. (02173) 8538-0 · Fax 853860 + 853870

J1 1401 EN


Technical Data Sheet - Product Information

Product: **NITRO - KOMBISPACHTEL**




Characteristics:

Fast drying one component fine putty on the basis of nitro-cellulose synthetic resin.
Well suited as a spot filler to remove small damages such as scratches or stone pitting and to smooth minor irregularities.
Adhesion on sheet steel, wood and glass-fibre reinforced car body parts based on polyester material.



Range of application:

Car-refinishing, motorbike repair, industry, wooden furniture




Chemical basis:

NITRO-KOMBISPACHTEL: Nitro-cellulose, synthetic resin, pigments and solvents.



Instructions for use:

Clean surface from dirt and grease. Remove rust and old lacquer coat.
Slightly rough up surface with abrasive paper or sand blast.
If applied in thin layers, the putty can be sanded after a drying time of approx. 30 minutes.
If thicker layers are required apply several thin coats and allow for approx. 1 hour drying time for each layer.




Untreated steel sheets:

Treat with anti-corrosion primer before the application of NITRO-KOMBISPACHTEL.

Pot life:

15 - 20 minutes



Temperature conditions:


Do not apply at temperatures below +10 °C

Disposal consideration:

Disposal of according to local regulations.

Sanding:

Paper P 80 - 280



Storage stability:

12 months in tightly closed tins when kept at +20 °C.

Please consider our technical advice – be it verbally, in writing or testing and supplied to the best of our knowledge – as information only and without responsibility in respect to other parties. It does not release you from your obligation to test the products supplied regarding their suitability for the intended application. Handling and utilization of our products by the customer exceed our responsibility and are at the customer's liability. We guarantee that our products conform to their specification and we will refund or replace non conforming products only. Airo cannot be held responsible for any damages or accidents in connection with the use of our product.